



STENCIL CLEANER 11

An alcohol-based cleaning fluid designed for manual pre-cleaning and cleaning of print stencils and squeegees.

Ready-mix designed for direct use.
Designed for cleaning of most soldering paste and SMT adhesive types.
Recommended for stencil pre-cleaning before machine cleaning or as a manual solution for stencil cleaning.

| Recommended areas for use | Recommended cleaning technology |
|---|---------------------------------|
| 1. Soldering paste residues | manual cleaning |
| 2. SMT adhesive residues | manual cleaning |
| 3. Other operating contaminants - dust, grease, etc | manual cleaning |

Process table

| Cleaning technology | Cleaning | 1. rinse | 2. rinse | Drying |
|---------------------|--------------------|----------|----------|------------|
| Manual cleaning | Stencil Cleaner 11 | - | - | with wiper |

Product information

- Universal solution for all types of soldering paste and most SMT adhesive types.
- High material compatibility
- Compatible with both lead and non-lead processes
- Environmentally friendly - biodegradable
- Does not contain tensides, no risk of solid residue occurrence on the cleaned part surfaces

Table of physical and chemical properties

| | |
|----------------------------------|---------------------|
| Product appearance: | colorless liquid |
| Odour, aroma: | etheric |
| pH: | not measurable |
| VOC content: | 100% |
| Recommended process temperature: | ambient temperature |
| Ignition temperature: | < 350°C |
| Flash point: | < -23°C |
| Density at 20°C: | 1,55 - 1,66 kg/l |



Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning

Date of issue:
1.11.2015

Detailed information can be found in the Safety Data Sheet of **Stencil Cleaner 11**.



STENCIL CLEANER 11



Packing

bottle: 1 litre; can: 5, 10, 25 litres



Transport

UN 1950



Handling

Turn the manual sprayer nozzle from position STOP to 90° before the first use. Then apply a necessary amount to the part to be cleaned, wait for several minutes and wipe residues using a smooth piece of cloth. Repeat the procedure, if necessary.



Storage

Should be stored in closed containers, in ventilated areas at the temperature from 5 to 25°C.



Best before

The maximum usable life for this product is 24 months from the production date.



RoHS
Compliant



REACH
SVHC



BIODEGRADABLE



Date of issue:
1.11.2015

Detailed information can be found in the
Safety Data Sheet of **Stencil Cleaner 11**.